



FDX XTREME

PREMIUM



TW Premium



TW 500 Premium

On request

Su richiesta kit avvolgitubo



NEW

**B&S
VANGUARD
ENGINES**
(18 or 31 HP)



RPM
deceleration kit

*Kit
deceleratore di
giri motore*

Rear wheel
with brake

*Ruota
posteriore
dotata di
freno*



FOR MORE INFO:
MAGGIORI INFORMAZIONI:





GENERAL FEATURES · CARATTERISTICHE GENERALI

- ø300mm 4 wheels with foamed-acting pneumatic
- Engines: Honda GX 690 or B&S Vanguard (18 or 31 HP)
- Gearbox (with 1560 rpm pump)
- Electrical starting
- No engine-oil safety device (oil-alert)
- Hours meter (on models with HONDA engine)
- Automatic decelerator to reduce the number of revs in the bypass phase
- Stainless steel gradual pressure restoration valve with EASY START
- Thermostatic valve
- Big water filter at pump inlet, readily serviceable cartridge type
- Water suction from external tank option (self-priming pumps)
- Suitable for high professional use
- 4 ruote schiumate ø300mm con effetto pneumatico
- Motori: Honda GX 690 oppure B&S Vanguard (18 o 31 HP)
- Riduttore di giri (con pompa a 1560 rpm)
- Avviamento elettrico
- Dispositivo di Sicurezza mancanza olio motore (oil-alert)
- Contatore (solo su modelli con motore HONDA)
- Deceleratore automatico per la riduzione del numero di giri in fase di by-pass
- Valvola a ripristino graduale della pressione in acciaio inox con EASY START
- Valvola termostatica
- Filtro acqua di grande dimensione in ingresso pompa a cartuccia ispezionabile
- Possibilità di aspirare acqua da serbatoio esterno (pompe autoadescenti)
- Uso altamente professionale

TECHNICAL FEATURES · CARATTERISTICHE TECNICHE

CODE CODICE	MODELS MODELLI	PUMP POMPA	MAX		WORK		I/h	HP kW		kg	(L x W x H) cm
			bar	MPa	bar	MPa		HP	kW		
9058 0025	FDX Xtreme 18/350 Vanguard B&S 18 HP	TW Premium	360	36	50÷350	5÷35	410÷1080	18,0	13,4	150	100 x 82 x 85
9058 0001	FDX Xtreme 15/500 Honda GX690	TW Premium 500	520	52	100÷500	10÷50	440÷990	22,0	16,4	150	100 x 82 x 85
9058 0002	FDX Xtreme 18/400 Honda GX690	TW Premium 500	415	41,5	50÷400	5÷40	380÷1080	22,0	16,4	150	100 x 82 x 85
9058 0003	FDX Xtreme 21/350 Honda GX690	TW Premium	360	36	50÷350	5÷35	480÷1260	22,0	16,4	150	100 x 82 x 85
9058 0004	FDX Xtreme 30/280 Honda GX690	TW Premium	280	28	50÷270	5÷27	770÷1800	22,0	16,4	150	100 x 82 x 85
9058 0005	FDX Xtreme 36/230 Honda GX690	TW Premium	230	23	30÷220	3÷22	800÷2160	22,0	16,4	150	100 x 82 x 85
9058 0006	FDX Xtreme 42/180 Honda GX690	TW Premium	180	18	30÷170	3÷17	1060÷2520	22,0	16,4	150	100 x 82 x 85
9058 0024	FDX Xtreme 21/500 Vanguard B&S 31 HP	TW Premium 500	520	52	100÷500	10÷50	560÷1260	31,0	23,1	150	100 x 82 x 85

STANDARD EQUIPMENT · DOTAZIONE STANDARD

 <p>GH 401 gun with Swivel (n.2 o-ring) Pistola GH 401 con Swivel (n.2 o-ring)</p>	 <p>L50 straight S.S. lance with ball quick coupler, without nozzles Lancia dritta L50 inox con attacco rapido a sfere, senza ugelli</p>	 <p>25° spray nozzle, 1/4" MEG connection Ugello con getto a lama 25° attacco 1/4" MEG</p>
 <p>GH 501 stainless steel spray gun with quick couplers Pistola GH 501 inox con attacchi rapidi</p>	 <p>Straight stainless steel lance, with adjustable handle Lancia inox dritta, con impugnatura regolabile</p>	 <p>Flat stainless-steel spray nozzle with ceramic insert Ugello inox getto piatto con inserto in ceramica</p>
 <p>Rubber delivery hose kit Kit tubo gomma mandata 10 m</p>	 <p>20 mt delivery hose kit with quick coupler M24x1,5 Kit tubo mandata 20 mt con attacchi rapidi M24x1,5</p>	 <p>Self cleaning water filter Filtro acqua autopulente</p>